



Digital
Duplicator

RISO SF5130  A
SF5030  A

130 ppm High-speed printing

300x600 dpi High-resolution

Legal/A4 print area

Speed Forward Edition II




An upgraded print system for use in various settings

Productivity

High-speed printing with excellent efficiency

High Speed 130 PPM* Printing

Printing at the high speed of 130 PPM, SF5130/5030 EII Series can finish 1000 pages in less than 8 minutes. The ever-increasing printed document requirements can be supported by the High Productivity of the machine



*Printing speed varies according to the model.



High Capacity Paper Feeding

With the Capacity of 1000 sheets for feeding & receiving, the machine operates for longer periods of time, without interruption


*When using the following weights of paper: 64 gsm to 80 gsm.



Overwhelmingly Economical Print Costs


Since the technology involves Master, as the number of prints increases the cost of printing keeps on reducing, making it ideal for multiple copy print requirements

Print quantity and cost per print



Multiple Page Printing

Page layout options in the Printer driver helps in combining multiple copies of the same page or copies of multiple pages onto a single printed page to save paper. It also allows conveniently condense bulky multiple page documents in an easy-to-read format.




Usability

Improved printing experience with convenient operability and various new functions

Paper Memory Print

Paper Memory Print is ideal when it is difficult to print directly from a PC or thru USB Flash drive. This function helps in improving the Confidentiality and helps to prevent information leak. The original data created on a PC is converted into a "Paper Memory Data". Scanning the data, the SF EII series retrieves the original data, achieving the same high quality of output image as that being processed through the PC.



Multiple Feed Detection

The machine keeps the operator informed, in case of a multiple paper feed is detected.

Various printing options

The SF EII series offers various ways of printing, apart from the regular method of Scanning the original document. The machine comes with a Standard Computer Interface & Printing thru a USB Flash Drive




Slip Sheet Sorting

The SF EII Series can be programmed to insert a blank page between sets or after designated number of pages printed. This makes easier to sort & segregate for further processing.

Easy to Use LCD Panel

The information on the 128 x 64 dot LCD panel can be easily viewed, which also displays the residual quantity of supplies to prevent an out-of-stock situation occurring.



Quality

Outstanding image quality with 600 dpi, providing clear text and images with smooth gradations.

High image quality D600 DPI printing

Improved resolution for both scanning and printing. This achieves sharp and clear output with the highest image quality.




Image data processing raises the bar for 600x600 dpi scanning and printing

This achieves sharp and clear output with high image quality.



Enhanced features for clearer output

High scanning quality


The scanner attains smooth tonal gradation even with photo

- Reduced blown-out highlights via equalized dot description images.

Image-processing function

Decreases image deterioration through improved image processing, delivering clearer output.

- Minimizes blocked-up shadows through enhanced gamma correction
- Sharp outlines with contour enhancement achieved




Other various functions for optimum output

- Auto base control
- Tone smooth function
- Four image-processing modes: Line, Photo, Duo, and Pencil

Ink color variations

21 standard colors, 50 custom colors and special order made colors are available. A wide range of printing colors



Sustainability

Energy saving and environmental considerations

Rice bran oil ink


The rice bran oil ink contributes to environmental sustainability. The biomass ratio of ink materials has been increased, which reduces the burden on the environment.

Rice bran, which would be otherwise wasted, is a raw material with no VOCs, so after the oil is extracted for the ink it can subsequently be used as fertilizer or animal feed.



RISO FII type inks are certified with environmental certification marks issued by ink industry groups in Japan.

[Manufacturing Process]



Energy saving

RISO Digital Duplicators do not use toners so a heater that is usually required for bonding toner to the paper is not necessary.

They employ automatic shut-off and sleep functions after a certain time interval elapses, to effectively reduce power consumption.

Eco-friendly


The SF EII series consumes 1/10th the energy, compared with energy star guidelines.

- ENERGY STAR® qualified and RoHS certified
- Complies with the ErP directive in Europe
- Consumes less power and produces less heat
- Energy-saving system




RISO SF5130 EII A SF5030 EII A


Optional Accessories



RISO FII Type Drum
Enables color printing.
(Case included)



RISO Auto Document Feeder AF-VII
Scans multiple documents automatically.



RISO Job Separator IV; NIII
Enables easy separation of printed sheets by inserting tape strips.



Card Feed Kit
Compatible with paper weight 100 gsm to 400 gsm.
*Please contact a RISO sales representative for the kinds of paper that may be used.



RISO Stand D Type III
Deluxe and with doors for convenient storage with a neat appearance.



RISO Stand N Type III
Sturdy open-front stand also offers convenient storage of consumables.

- IC Card Reader Activation Kit RG
 - RISO Network Kit S10
 - RISO Printer driver for Macintosh
 - Envelope Feed Kit
- Compatible with paper weight 50 gsm to 120 gsm.

RISO iQualitySystem™



The RISO i Quality mark indicates a RISO product compatible with the RISO i Quality System.



RISO INK FII Type Color (1000 ml)



RISO MASTER FII Type
(LEGAL: 250 sheets | A4: 295 sheets)



RISO INK FII Type Black (1000 ml)

Specifications

Model	SF5130 EII	SF5030 EII
Master Making/Printing Methods	High-speed digital master-making/Fully automatic printing	
Original Type	Book or sheet	
Master Making Time*1	Quick Master Making mode	Approx. 18 seconds (A4, short-edge feed)
	Normal Master Making mode	Approx. 20 seconds (A4, short-edge feed)
Resolution	Scanning	600 dpi × 600 dpi
	Printing	300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
Maximum Scanning Area	297 mm × 432 mm	
Print Paper Weight	46 gsm to 157 gsm	
Print Paper Size	100 mm × 148 mm to 310 mm × 432 mm	
Maximum Printing Area	251 mm × 357 mm	210 mm × 290 mm
Paper Feed Tray Stacking Capacity	1000 sheets*2, stacking height of 110 mm or lower	
Paper Receiving Tray Stacking Capacity	1000 sheets*2, stacking height of 110 mm or lower	
Print Speed	5 levels: 60, 80, 100, 120 and 130 ppm	
Print Position Adjustment	Horizontal: ±15 mm, Vertical: ±10 mm	
Image Processing Mode	Line, Photo, Duo, Pencil	
Print Reproduction Ratio	Zoom (50% to 200%), 100% reproduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%)	
User Interface	LCD panel	
Functions	Original Scanning Mode, Scanning Level, Enlargement/Reduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF Semi-Auto*3, Speed, Density, Print Position, Program A/B, D-Feed Check, Slip Sheet Sorting, Job Separation*4, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Paper Memory Print, Auto Sleep Setting, Auto Power-OFF Setting, ECO Mode, RISO iQuality System	
PC Interface	USB2.0, Ethernet:100BASE-TX, 10BASE-T*5	
Ink Supply	Full automatic (1000 ml/cartridge)	
Master Supply/Disposal	Full automatic (B4: approx. 250 sheets per roll)/Disposal capacity: approx. 100 sheets	
Power Source*6	AC 100-120 V 3.4 A, AC 220-240 V 1.6 A, 50-60 Hz	
Power Consumption	Standard	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	Optional Accessories Connected*7	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
Dimensions (W×D×H)	In use	1415 mm × 670 mm*8 × 1065 mm*9
	In storage	780 mm × 670 mm*8 × 1065 mm*9
Required Space (W×D×H)	1415 mm × 1240 mm × 1515 mm*9	
Weight	100 kg*10	

*1 Measurement value when set to 100% reproduction ratio.

*2 When using the following weight of paper; 64 gsm to 80 gsm

*3 Usable when the optional auto document feeder is installed.

*4 Usable when the optional Job Separator is installed.

*5 RISO Network Kit S10 (optional) is required for connecting to the network.

*6 To switch between 100-120 V and 220-240 V, contact your dealer or authorized representative.

*7 When all the following optional accessories are installed; Auto Document Feeder, Job Separator, IC Card Reader.

*8 The depth does not include the stabilizers for the dedicated stand.

*9 The height includes the dedicated stand.

*10 The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

As per Govt. of India, E-Waste rule 2016, after the end of life of Riso Product(s), kindly intimate Riso India Pvt. Ltd. at product-recycling@risoindia.com or log on to website (www.risoindia.com) to make arrangement to pick up the End of Life product (E-Waste) via its authorised recycler.



Product Video

and RISO, RISO i Quality System and RISO i Quality mark are trademarks or registered trademarks of RISO KAGAKU CORPORATION in the United States and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.
Copyright ©2019 RISO KAGAKU CORPORATION. All rights reserved.

For more details please contact:

RISO INDIA PRIVATE LIMITED (HEAD OFFICE)

D7(Ground Floor), Sector-3, Noida-201301, Uttar Pradesh

Tele : +91-120-4721300 | Email : contact@risoindia.com | Web : www.risoindia.com



RISO KAGAKU CORPORATION
5-34-7 Shiba, Minato-ku, Tokyo 108-8385 Japan
<https://www.riso.com/>